

2-Speed Impact Drills

Come complete with:

Depth gauge, Auxiliary handle, Keyed chuck.



BUR2 350CET

BUR2 350E

Technical Data

Model:		BU2 350	BUR2 350E	BUR2 350CET
Capacity in (1 / 2 Gear)				
- concrete:	mm	16 / 10	16 / 10	16 / 10
- steel:	mm	16 / 10	16 / 10	16 / 10
- non-ferrous metals:	mm	20 / 13	20 / 13	20 / 13
- wood:	mm	45 / 20	45 / 20	45 / 20
No load rpm:	min ⁻¹	800 / 2000	0-800 / 0-2000	250-800 / 625-2000
No load impact rate:	min ⁻¹	36000	36000	36000
Max. torque:	Nm	65	65	65
Spindle thread:	UNF	1/2"-20	1/2"-20	1/2"-20
Chuck capacity:	mm	3-16	3-16	3-16
Journal diameter:	mm	43	43	43
Screw for wood, max.:	mm	-	Ø8, L=100	Ø8, L=100
Weight:	kg	3.3	3.5	3.3
Power input:	W	1010	1010	1010
Cat. N		12000030100	12000030302	12000030502



SPARKY Power Tools GmbH
 20, Leipziger Strasse
 10117 Berlin, Germany
 Tel.: +49 30 203916-0
 Fax: +49 30 203916-66
 E-mail:
 powertools@sparkygroup.com