

BUR2 250E • BUR2 250CET



SPARKY

HD PROFESSIONAL

2-Speed Impact Drills

Come complete with:

Depth gauge, Auxiliary handle, Keyed chuck. Option: Keyless chuck



Technical Data

Model:	BUR2 250E	BUR2 250CET
Capacity in (1 / 2 Gear)		
- concrete:	25 / 13 mm	25 / 13 mm
- steel:	16 / 10 mm	16 / 10 mm
- non-ferrous metals:	20 / 6 mm	20 / 6 mm
- wood:	40 / 25 mm	40 / 25 mm
Electronic speed pre-selection:	Yes	Yes
Constant electronics:	No	Yes
Non-self start protection:	No	Yes
No load rpm:	0–1000 / 0–2900 min ⁻¹	0–1000 / 0–2900 min ⁻¹
No load impact rate:	18000 / 52200 min ⁻¹	18000 / 52200 min ⁻¹
Max. torque:	46 Nm	46 Nm
Spindle thread:	1/2"-20 UNF	1/2"-20 UNF
Chuck capacity:	1.5–13 mm	1.5–13 mm
Journal diameter:	43 mm	43 mm
Screw for wood, max.:	Ø6, L=100 mm	Ø6, L=100 mm
Weight:	2.7 kg	2.7 kg
Power input:	1010 W	1010 W



SPARKY Power Tools GmbH

20, Leipziger Strasse
10117 Berlin, Germany
Tel.: +49 30 203916-0
Fax: +49 30 203916-66
E-mail: powertools@sparkygroup.com