

BP 330E • BP 330CE



SPARKY

HD PROFESSIONAL

SDS-Plus Rotary Hammer

Comes complete with:
Plastic case; Anti Vibration auxiliary handle; Depth gauge




HEAVYDUTY




2 modes: Hammer Drilling and Chiselling

BP 330E



Electronic regulator of rotation speed

BP 330CE



Electronic speed pre-selection
Constant electronics

LED overload indication

LED 8 Hour brush wear out indicator



Technical Data

Model:	BP 330E	BP 330CE
Power input:	900 W	900 W
Capacity in Concrete:	30 mm	30 mm
Core cutter capacity in concrete:	80 mm	80 mm
No load rpm:	380–830 min ⁻¹	380–660 min ⁻¹
No load rpm in "High Power":	–	750 min ⁻¹
No load impact rate:	1560–3400 min ⁻¹	1640–2970 min ⁻¹
Impact rate in "High Power":	–	3230 min ⁻¹
Impact energy (EPTA Procedure 05/2009):	3.5 J	3.3 J
Impact energy in "High Power" (EPTA Procedure 05/2009):	–	4.2 J
Max. torque:	60 Nm	60 Nm
Weight:	3.7 kg	3.9 kg



SPARKY Power Tools GmbH

20, Leipziger Strasse
10117 Berlin, Germany
Tel.: +49 30 203916-0
Fax: +49 30 203916-66
E-mail: powertools@sparkygroup.com